



SECTION VIEW A-A
(SCALE 1:5)

REVISION HISTORY

REV	DATE	DESCRIPTION	BY	CHKD
1	15/01/2021	CREATED	PH	

INSTALLATION DESCRIPTION

1. MAKE AN OPENING IN WALL TO DIMENSIONS DETAILED ON DRAWING.
2. MARK THE FIXING POINTS ON THE WALL.
3. DRILL 4x HOLES IN THE MARKED POSITIONS.
4. HOLD THE SHELF UP TO THE HOLES AND RETAIN WITH 4x NO12x2" TORX S/STEEL SECURITY CNSNK SELF TAPPER (SUPPLIED). FOLLOW SUITABLE GUIDELINES FOR THE WALL MATERIAL ONSITE TO RETAIN SHELF.
5. GRADUALLY TIGHTEN THE FIXINGS IN STAGES SO NOT TO STRESS THE SOLID SURFACE MATERIAL.
6. APPLY A SUITABLY APPROVED ANTI-PICK MASTIC TO SEAL THE SHELF TO THE WALL. THE SHELF HAS 5mm WIDE FLATS ON ALL EDGES TO AID WITH THIS.
7. USE A SUITABLE TOOL TO PROFILE THE MASTIC TO THE ANGLED PROFILE OF THE PRODUCT.

© 2021 Copyright THIS DRAWING IS THE PROPERTY OF WALLGATE LIMITED AND IS ISSUED ON THE STRICT UNDERSTANDING THAT THE INFORMATION CONTAINED WILL NOT BE REPRODUCED, COPIED OR USED WITHOUT PRIOR AGREEMENT OF WALLGATE LTD.



TITLE: RECESSED SOLID SURFACE SHELF

Drg No: ALF-04 V3

Model/Client/Project:

MATERIAL: SOLID SURFACE

FINISH: SILK POLISH

SHEET 1 OF 1

Limits: (unless stated)
 ± 0.25mm (sheetmetal)
 ± 0.10mm (machined)
 ± 2.00mm (pattern)
 ± 5.00mm (moulded)

All dimensions in mm,
 All angles 90° (unless stated)

SCALE: 1:5

A4 3rd