

MODEL CWU 01 CLASSIC URINAL

SPECIFICATION SHEET

INSTALLATION

The CWU_01 pod urinal is designed for surface mounting with rear entry services & wall fixings. Three M10 fixing points are provided with 175mm long bolts suitable for a 150mm thickness wall panel.

WASTE

The urinal is supplied with a 32mm nominal ID pipe tail, 250mm long. This should be connected to a deep seal waste trap suitable for 1 ¼" (32mm) waste pipe. A range of traps are available from Wallgate.

WATER

A chrome finish spreader is supplied which has a ½" BSP male thread connection. The supply feed must be fed from behind the urinal & through the wall.

CISTERN

Mount the cistern 1.37m from its base to the top of the urinal lip.

Number of urinals per cistern:

Bowls:	Cistern size (Litres):
◆ 1-2	4.5
◆ 3	9.0
◆ 4-5	13.6

DIMENSIONS

Weight: 14kg

Size: H435 x W310 x D270mm

APPROVALS

Complies with BS5520.1977 (for Vitreous china bowl urinals) BS476 Pt 6 Class 0 & 7 Class 1 – non inflammable rating.

ISO EN 19712-3-2007 rated 5 for durability, stain resistance, cigarette burns etc

OPTIONS (contact Wallgate sales for details).

1. Divider panel as shown on drawing below P/No CWD_01.
2. Cisterns for concealed or exposed installations.
3. Flush pipes for concealed or exposed installations.
4. Waste traps.

